

SCRUBBER DRYERS - RIDE ON

CT140e

MAX PRODUCTIVITY

5740

 m^2/h

3 h

BATTERIES

RUNNING TIME

WATER TANK RUNNING TIME

90'

working session



PAD HOLDER AND BRUSH STANDARDLY INCLUDED

MOST FREQUENTLY USE

SELLING POINTS

RETAIL







HORECA

D. 4. 67-0.D.C

CLEANING CONTRACTORS

MUNICIPALITIES

SPECS







Sports steering wheel

Side splash guard

Anti-collision wheel

TECHNICAL DATA

| | | CT140e BT70 | CT140e BT70 |
|---|---------|------------------|-------------------|
| Code | | STN800052301 | STN8000523 |
| PERFORMANCE | | | |
| Max theoretical productivity | m²/h | 5740 | 5740 |
| Cleaning path | mm | 700 | 700 |
| Water tank capacity (solution / recovery) | T. | 110/130 | 110/130 |
| Max running time | min | 240 | 240 |
| Voltage | V-Hz-Ah | 24/12V-200Ah AGM | 24/12V-200Ah AGM |
| Installed power | W | 2850 | 2850 |
| Brush pressure | kg | 0 - 110 | 0 - 110 |
| Squeegee width | mm | 960 | 960 |
| Max speed | km/h | 6 | 6 |
| Weight | kg | 320 | 452 |
| Dimension (LxWxH) | mm | 1480x860x1230 | 1480x860x1230 |
| Batteries | | no | 4 x 6 V 200Ah AGM |
| Battery Charger | | no | Stand alone |

| STANDARD EQUIPMENT | | CT140e BT70 |
|--------------------|-----|--------------------|
| BRUSHES | | |
| PPL SOFT | 2 x | CN5002582 |
| | | |
| SQUEEGEE BLADES | | |
| LATEX FRONT BLADE | | CN5002305 - 998mm |
| LATEX REAR BLADE | | CN5002304 - 1046mm |