



SCRUBBER DRYERS - WALK BEHIND

CT56e

MAX PRODUCTIVITY

2520

m²/h

BATTERIES
RUNNING TIME

3 h

WATER TANK
RUNNING TIME

45'
working session



PAD HOLDER AND BRUSH STANDARDLY INCLUDED

MOST FREQUENTLY USE



SELLING POINTS



SPECS



Automatic brush
release and attachment



560 mm brush



user-friendly control panel

TECHNICAL DATA

| | | CT56e BT56 | CT56e BT56 |
|---|-------------------|-------------------|--------------------|
| Code | | STN800052801 | STN8000528 |
| PERFORMANCE | | | |
| Max theoretical productivity | m ² /h | 2520 | 2520 |
| Cleaning path | mm | 560 | 560 |
| Water tank capacity (solution / recovery) | l | 50/50 | 50/50 |
| Max running time | min | 60 | 60 |
| Voltage | V-Hz-Ah | 24/12V-100Ah AGM | 24/12V-100Ah AGM |
| Installed power | W | 1350 | 1350 |
| Brush pressure | kg | 19 | 19 |
| Squeegee width | mm | 770 | 770 |
| Max speed | km/h | 3.5 | 3.5 |
| Weight | kg | 83 | 150 |
| Dimension (LxWxH) | mm | 1250x580x980 | 1250x580x980 |
| Batteries | | no | 2 x 12 V 100Ah AGM |
| Battery Charger | | no | Stand alone |

STANDARD EQUIPMENT**CT56e BT56****BRUSHES**

| | |
|----------|-----------|
| PPL SOFT | CN5002557 |
|----------|-----------|

SQUEEGEE BLADES

| | |
|-------------------|-------------------|
| LATEX FRONT BLADE | CN5002301 - 798mm |
| LATEX REAR BLADE | CN5005102 - 850mm |