



PURE WATER CLEANING SYSTEM

# HPE HIGH PURE

PRESSURE

10 bar

FLOW RATE

8 l/min



## EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ POWER PUMP
- ▶ MANOMETER

## TECHNICAL DATA

		HPE
Code		APTA40015
PERFORMANCE		
Operating pressure	bar	8-10
Pure water flow	l/min	3-8
Water in/out connections	gas	3/4"
Max poles lenght	m	16 (also with 2 poles)
Productivity	m <sup>2</sup> /h	up to 200
Power supply	Ph-V-Hz	1-230-50
Absorbed power	kW	0,6
Dimension (LxWxH)	cm	53x50x127
Weight	kg	55

## MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/  
TENSILE STRUCTURES

## STANDARD EQUIPMENT

CODE: FTAC40002  
REVERSE OSMOSIS  
MEMBRANE



CODE: PRCH400034  
POWDER FOR  
OSMOTIC MEMBRANE  
FILTER MAINTENANCE



CODE: KTRI40106  
FILTER KIT: 1PCS SEDIMENTATION,  
1PCS ACTIVE CARBON, 1PCS  
DEIONIZING RESIN CARTRIDGE



CODE: VVSF40018  
FLOW ONTROL VALVE



CODE: TBFX40009  
30 m FLEXIBLE HOSE  
WITH FITTINGS



CODE: CNPR40007  
GASKET LUBRICANT



CODE: AZMC40006  
HAND-HELD TDS  
METER



CODE: TBBP40010  
DRAINAGE TUBE

