

## **SCRUBBER DRYERS - RIDE ON**

CT125e

MAX PRODUCTIVITY

4800

BATTERIES RUNNING TIME

3 h

WATER TANK RUNNING TIME

100'

working session

 $m^2/h$ 



PAD HOLDER AND BRUSH STANDARDLY INCLUDED

## MOST FREQUENTLY USE

## **SELLING POINTS**

RETAIL

SELF LEVELING SYSTEM


**HORECA** 

**CLEANING CONTRACTORS** 

MUNICIPALITIES









Elecromagnetic brake



Anti-rollover system

## TECHNICAL DATA

		CT125e BT80	CT125e BT80
Code		STN800052201	STN8000522
PERFORMANCE			
Max theoretical productivity	m²/h	4800	4800
Cleaning path	mm	800	800
Water tank capacity (solution / recovery)	T	105/110	105/110
Max running time	min	240	240
Voltage	V-Hz-Ah	24/12V-200Ah AGI	V 24/12V-200Ah AGM
Installed power	W	2200	2200
Brush pressure	kg	36	36
Squeegee width	mm	1120	1120
Max speed	km/h	6,5	6,5
Weight	kg	236	368
Dimension (LxWxH)	mm	1500x900x1330	1500x900x1330
Batteries		no	4 x 6 V 200Ah AGM
Battery Charger		no	Stand alone

STANDARD EQUIPMENT		CT125e BT80
BRUSHES		
PPL SOFT	2 x	CN5002539
SQUEEGEE BLADES		
LATEX FRONT BLADE		CN5002300 - 1156mm
LATEX REAR BLADE		CN5002299 - 1210mm